




# External door mount



# HEX100PC series

## **Dimension drawing**



#### Features

- ♦ IP55 waterproof at external side
- "One touch" dry run test and dust cleaning
- Standalone temperature control
- Clear LED status indicator
- Dry contact alarm output

### Design

- ♦ Air to air heat exchange
- Rated voltage at 48V
- Reduntant fan quantity design
- High efficiency and reliable fan
- Easy installation and maintenance

Main feature Unit Specification mm 690 x 360 x 242 Dimension (H x W x D) (27 x 14 x 10) (inch) Cooling capacity<sub>\*Note</sub> W/K (W/°F) 70 (39) 90 (50) **Rated voltage** VDC 48 **Operating current** 3.6 Α 1.7 173 **Opearting power** W 82 **Operating voltage range** VDC 40 ~ 60 °C Operating temperature range -10 ~ +65 Noise (1.5 meter) dB-A 65.0 70.0 Weight 13 (29) Kg (Lb)

\* Note : The cooling capacity (W/K , W/°C or W/°F) is defined as Q/ (TI-TA)

Q : Heat dissipation (W) from inside of cabinet

TI : Return temperature of internal air circuit (K , °C or °F)

- TA : Ambient temperature of external air circuit (K , °C or °F)
- \* Specifications are subject to change without notice.