



Door Mounting type



HEX150PB series

Dimension drawing





Features

- IP55 waterproof at external side
- One touch" dry run test and dust cleaning
- Optional communication function design
- Easy installation and maintenance from internal side
- Clear LED status indicator
- High efficiency and reliable fan modules

Design

- Air to air heat exchange
- Door mounted
- Rated voltage at 48V
- Complete airtight design for outdoor application
- Drainage hole in the bottom
- Reduntant fan quantity design

Main feature	Unit	Specification
Dimension (H x W x D)	mm	640 x 550 x 278
Cooling capacity	W/K	150 (MAX.) _{*Note}
Rated voltage	Vdc	48 (TYP.)
Operating voltage range	Vdc	40 ~ 60
Rated current	Α	5.8 (MAX.)
Power consumption	w	278.4 (MAX.)
Operating temperature range	°C	-10 ~ +65
Internal airflow	CFM	480
External airflow	CFM	630
Weight	Kg	20.0

278.0 (MAX.)

235.0

UNIT:MM

* Note : The cooling capacity (W/K OR W/°C) is defined as $Q/(T_I-T_A)$

Q : Heat dissipation (W) from inside of cabinet

- T_I : Return temperature of internal air circuit (K OR °C)
- T_A : Ambient temperature of external air circuit (K OR °C)
- * Specifications are subject to change without notice.